



Filtration Solutions for Bottle Washing Machines



BOLLFILTER Automatic for your washing process. Maximum plant protection. Minimum operating costs.



Our filters in your washing process



6.64 BWM/6.60 BWM caustic soda solution filter

The BOLLFILTER Automatic Type 6.64 BWM/6.60 BWM offers top results for the filtration of caustic soda solutions and requires only limited maintenance. It is not necessary to pause the process, thanks to the multi chamber principle. The filtration and backflushing processes can run in parallel. Efficient washing intervals with minimum backflushing volumes keep on-going operating costs low.



6.18 BWM spray nozzle protection

The operating principle of the BOLLFILTER Automatic Type 6.18 BWM is based on a filter candle that is open at each end. Blocked washing nozzles are a thing of the past because dirt particles are efficiently trapped on the inside surface of the filter candle.

The continuity of the filter process guarantees a fully automatic differential pressure or time-controlled backflushing unit.



6.03 AOT disinfection/filtration

The BOLLFILTER Automatic Type 6.03 AOT provides the solution to two different challenges in a unique manner. Its primary function is to efficiently remove contamination from your application. In addition, the filter candle disinfects the process water using UV radiation. Here, reactive free radicals ensure the chemical-free, oxidative degradation of biological components such as bacteria. The UV system replaces treatment using biocides and is more cost-efficient at the same time.

A clean solution – plant efficiency on the next level



Application expertise for washing machines of any size

With BOLL & KIRCH you have an expert partner for multifaceted applications in the beverage industry – we understand your specific bottle washing process and protect the components using automatic filtration solutions.

ABInBev

Through the use of BOLLFILTERs at ABInBev in China, it has been possible to increase line production by 3.32%. This equates to an additional output of 9,000 bottles per hour.


Darguner Brauerei

By using the BOLLFILTER Automatic Type 6.64 BWM at the Darguner Brauerei (Dargun Brewery) it has been possible to reduce the level of contaminants in the main caustic bath by 47% and in the post-caustic bath by 65%. This has quadrupled the lifetime of the caustic solution and increased productivity.





Bottle washing machine



BOLLFILTER for maximizing the life of the main caustic bath

Cost-efficiently maintaining the continuity of complex cleaning processes: Automatic filters from BOLL & KIRCH satisfy the exacting requirements placed on bottle washing machines and efficiently protect the overall plant.

BOLLFILTERs can sustainably improve the hygiene and cleaning result of your system through guaranteed filtration quality, the automatic backflushing function and low-maintenance design. This achieves lasting spray nozzle protection and a reduction in the overall degree of contamination in your plant. The increased life of the main caustic bath is the result of the improved conditions.

BOLLFILTER Automatic filters can be integrated into bottle washing machines of practically any type. Either as an upgrade to your existing machine or as part of a new one – our flexible filtration solutions will meet your requirements while minimizing your on-going costs.


Primary benefits:

- · Defined filtration quality
- Increase in the life of the main caustic bath
- Minimisation of operating costs
- Improved plant availability
- Reduction of maintenance costs with a simultaneous increase in productivity
- Reduction in particle carryover

Filter sizes according to machine size

Caustic bath volume (m³)	Bottles per hour (btl/h)	Filter size
above 36 m³	above 40,000	6.64 BWM DN125
18 - 36 m³	15,000 – 40,000	6.64 BWM DN100
up to 18 m³	up to 15.000	6.64 BWM/6.60 BWM DN50

Tunnel pasteurisers



Filtration and disinfection in perfect interplay

One application, two benefits: The BOLLFILTER Automatic Type 6.03 AOT facilitates disinfection of the process water from your tunnel pasteuriser or cooling tower in addition to ensuring efficient permanent filtration. Using the AOT method, microorganisms are swiftly and effectively killed without the use of chemical additives.


The system can be integrated into your specific process via an interface in the cooling circuit of your tunnel pasteuriser or cooling tower. If disinfection is not necessary, the BOLLFILTER Automatic Type 6.18 BWM can be used to protect the spray nozzles.

Primary benefits:

- · Compact, multi-functional design
- · Reduced use of chemicals
- · Minimisation of operating costs
- Prevention of algal bloom



Crate washer



Reliable spray nozzle protection at low cost

Cleaning drink crates cost-efficiently and reliably: Operating and maintenance costs are reduced to the minimum thanks to a self-cleaning filtration system. Protecting your cleaning nozzles is always in the foreground here.





BOLL & KIRCH sets the standards for the filtration of process fluids in the beverage industry with its leading-edge products. Our comprehensive and ongoing approach to engineering guarantees self-cleaning filtration solutions that raise the overall plant efficiency for your specific application through

- · improved cleaning results,
- · effective plant protection and
- significantly minimising costs

Our customers trust in the flexibility of our processes when implementing application-optimised solutions, and value personal consultation as well as reliable service.

Contact:

BOLL & KIRCH Filterbau GmbH Siemensstraße 10 – 14 50170 Kerpen

Telephone: +49 2273 562 0

Fax: +49 2273 562 223 E-mail: info@bollfilter.de

www.bollfilter.com

